

Tipologia / Type of material:

 Gres porcellanato smaltato Rettificato/Glazed porcelain stoneware Rectified - **Group Bla GL** - Annex G - EN 14411
















Destinazione d'uso del materiale/Intended use of the material:

Piastrelle ceramiche per pavimenti interni ed esterni / Floor tiles for interior and exterior use

 FORMATO NOMINALE/NOMINAL SIZE (mm) **900x900x9**

 SERIE/SERIAL NAME **ELEGANCE**

 ARTICOLO/ARTICLE **CALACATTA MARBLES**

	Caratteristiche/Features	Metodo di prova/ Test method	Valori dichiarati/ Declared values
Dimensioni/Dimensions (W = Dimensione di Fabbricazione/Work Size)	Lunghezza e larghezza/Length and width		UNI EN ISO 10545-2 W ± 0,3 %; max ± 1,0 mm
	Spessore/Thickness		UNI EN ISO 10545-2 W ± 5 %; max ± 0,5 mm
	Rettilinearità dei lati/Straightness of sides		UNI EN ISO 10545-2 W ± 0,3 %; max ± 0,8 mm
	Ortogonalità/Rectangularity		UNI EN ISO 10545-2 W ± 0,3 %; max ± 1,5 mm
	Planarità/Surface flatness		UNI EN ISO 10545-2 W ± 0,4 %; max ± 1,8 mm
Fisiche/Physical	Assorbimento/Water absorption E _v		UNI EN ISO 10545-3 ≤ 0,5 %
	Forza di rottura/Breaking strength		UNI EN ISO 10545-4 ≥ 1300 N
	Modulo di rottura/Modulus of rupture		UNI EN ISO 10545-4 ≥ 35 N/mm ²
	Resistenza abrasione superficiale /Resistance to surface abrasion		UNI EN ISO 10545-7 PEI 5
	Resistenza agli sbalzi termici/Thermal Shock resistance		UNI EN ISO 10545-9 Resistant
	Resistenza al gelo/Frost resistance		UNI EN ISO 10545-12 Resistant
	Scivolosità/Determination of slip resistance		- NPD
Reazione al fuoco/Fire reaction		- A1 _{fl}	
Chimiche/ Chemical	Resistenza macchie - classe/Stain resistance - class		UNI EN ISO 10545-14 5
	Resistenza ai prodotti chimici d'impiego domestico/Resistance to household chemical products		UNI EN ISO 10545-13 A